

# EZEE SHINE

## HIGH SPEED FLOOR FINISH

**EZEE SHINE** is specifically formulated as a high speed floor finish. It contains a modified acrylic metalcomplexed polymer, and a wax as the basic ingredients. This product is based on the most recent technology for designing high performance tough floor finishes. This new technology provides finishes with improved performance profiles that include: Slip Resistance (ASTM D2047) greater durability, longer gloss retention, better scuff resistance, improved recoatability, easier removability and enhanced detergent resistance.

**DIRECTIONS:** Use on asphalt, vinyl, linoleum, terrazzo, properly sealed wood, and similar type floor surfaces. Preparation of the surface is of paramount importance. Thoroughly scrub and clean with a heavy duty cleaning solution. Use stripper to remove old wax and floor finish. After the floor has been rinsed and completely dry, apply a thin coat of floor finish with a wet mop used exclusively for this purpose. Fill a container or bucket with wax, soak the mop thoroughly and apply by using figure eight motions with the mop to insure complete coverage. Allow to dry approximately 30 minutes between applications of coats. For maintenance, it responds well to occasional low and high speed burnishing. Approximate coverage is 2500 square feet per gallon.

**CAUTION:** Avoid prolonged contact with vapors. Use in well-ventilated area. Avoid contact with eyes, skin and clothing. Harmful if swallowed. Eye protection and rubber gloves are recommended for handling. If eye contact occurs flush with water for 15 minutes and seek medical attention. Consult MSDS for further information.

Please Follow Good Safety  
Practices

**KEEP THIS AND ALL CLEANING PRODUCTS OUT OF THE  
REACH OF CHILDREN**

JANITORIAL



KEMPER INDUSTRIES, INC.  
2197 Stanton Road  
Daphne, AL 36526  
(866) 536-4225

[www.kemperindustries.com](http://www.kemperindustries.com)