

FLEET WASH

CONCENTRATED TRUCK WASH FORMULA

FLEET WASH is a super concentrated formulation proven to be effective in removing road film formed on over the road trucks. It contains inhibitors to prevent etching of glass, aluminum trim, and paints. It is a high foaming compound that contains no harsh alkalis. **FLEET WASH** should be diluted for economy, but delicate surfaces will not be harmed if the user accidentally uses too much detergent. It will not streak automotive surfaces.

FLEET WASH is fortified with a blend of liquid detergents designed to penetrate and remove road film and grime. It works well in cold, hot and hard water conditions.

DIRECTIONS FOR USE:

FLEET WASH should be diluted for economy. Because all jobs are different, the following guideline is given as a starting point and should be modified to suit the conditions at hand. In brush type cleaning, rinse the vehicle to remove any heavy grit that may scratch the surface, before washing.

HAND WASHING:	DILUTE 10:1
MECHANICAL WASHERS:	DILUTE 50:1
PRESSURE WASHERS:	DILUTE 25:1

CAUTION:

EYE AND SKIN IRRITANT

In case of contact with eyes or skin, flush with water for 15 minutes. If irritation persists seek medical attention. If swallowed drink large quantities of water. Get medical attention. Consult MSDS for additional information.

Please Follow Good Safety
Practices

**KEEP THIS AND ALL CLEANING PRODUCTS OUT OF THE
REACH OF CHILDREN**

INDUSTRIAL



KEMPER INDUSTRIES, INC.
2197 Stanton Road
Daphne, AL 36526
(866) 536-4225

www.kemperindustries.com