

FLOOR STRIPPER-SS

SUPER STRENGTH FLOOR STRIPPER

FLOOR STRIPPER-SS This strong floor stripper is designed to penetrate and dissolve floor finish and prepare floors for recoating without need of machine scrubbing. This procedure saves one-third to one-half the time required using ordinary strippers. It is designed to penetrate, dissolve, and suspend old floor finish and floor sealer for removal with wet vac or mop.

DIRECTIONS: The use dilutions range from (12oz) per gallon (16oz) per gallon depending on how much floor finish needs to be removed. The stripper should be diluted with cool water for best results. Apply stripper solution to floor using liberal amounts and ensure that solution is uniformly distributed. Do not allow stripper to dry on floor before removing. After stripper has been on floor for approximately four minutes, agitate with mop. Pick up all solution with a clean mop, wet vac or an automatic scrubber. After drying apply floor finish or sealer using normal procedures.

CAUTION: Avoid prolonged contact with vapors. Use in well-ventilated area. Avoid contact with eyes, skin and clothing. Harmful if swallowed. Eye protection and rubber gloves are recommended for handling. If eye contact occurs flush with water for 15 minutes and seek medical attention. Consult MSDS for further information.

Please Follow Good Safety
Practices

**KEEP THIS AND ALL CLEANING PRODUCTS OUT OF THE
REACH OF CHILDREN**

JANITORIAL



KEMPER INDUSTRIES, INC.
2197 Stanton Road
Daphne, AL 36526
(866) 536-4225

www.kemperindustries.com