

SURE SEAL

ACRYLIC/URETHANE FLOOR SEALER

SURE SEAL is specifically formulated as an interior/exterior acrylic/urethane-based sealer. This product is based on the most recent technology for designing high performance strong water-based sealers. This new technology provides a sealer with improved performance profiles that include: Slip Resistance (ASTM D2047) greater durability, longer gloss retention, better scuff resistance, improved recoatability, easier removability and enhanced detergent resistance.

DIRECTIONS: Use on resilient tile and terrazzo floors, asphalt, and similar type floor surfaces. Preparation of the surface is of paramount importance. Thoroughly scrub and clean with a heavy duty cleaning solution. After the floor has been rinsed and completely dry, apply a thin coat of **SURE SEAL**, apply by normal mopping method or a micro fiber applicator to insure complete coverage. Allow to dry approximately 30 minutes between applications of coats. For maintenance, it responds well to occasional low and high speed burnishing. Approximate coverage for the first coat is 800 square feet per gallon then a 1500 square foot are with the second coat.

CAUTION: Avoid prolonged contact with vapors. Use in well-ventilated area. Avoid contact with eyes, skin and clothing. Harmful if swallowed. Eye protection and rubber gloves are recommended for handling. If eye contact occurs flush with water for 15 minutes and seek medical attention. Consult MSDS for further information.

Please Follow Good Safety
Practices

**KEEP THIS AND ALL CLEANING PRODUCTS OUT OF THE
REACH OF CHILDREN**

JANITORIAL



KEMPER INDUSTRIES, INC.
2197 Stanton Road
Daphne, AL 36526
(866) 536-4225

www.kemperindustries.com